Rubiomonocoat ACCELERATOR - COMP. B

DESCRIPTION:
Rubio Monocoat Accelerator - Comp. B is added to the Rubio Monocoat oils for quicker drying and curing and for a stronger end result. **RMC Accelerator - Comp. B** is compatible with all the oils in the Rubio Monocoat range, with the exception of the RMC Invisible Oil System. Using **RMC Accelerator - Comp. B** is recommended for all applications, horizontal and vertical, where a quicker drying time and increased durability are desired (parquet, work surfaces, stairs, damp spaces, etc.).

SPECIFIC FEATURES:
- Miscible with all Rubio Monocoat oils (with the exception of the RMC Invisible Oil System)
- 0% VOC!
- Does not contain water
- Improves the wear-resistance of the finish
- Quick drying and hardening!
- Does not change the colour of the oil
- Does not affect the usage of the oil

INSTRUCTIONS:
- Having prepared the surface according to the guidelines (see technical data sheet of relevant product), mix the chosen oil with **RMC Accelerator - Comp. B** in the following proportions:
  > With **RMC Oil + 2C**: add max 30 % **RMC Accelerator - Comp. B**
  > With **RMC Hybrid Wood Protector**: add max 10 % **RMC Accelerator - Comp. B**
- Mix the oil and the **RMC Accelerator - Comp. B** well.
- Apply the chosen finish (see technical data sheet of relevant product).

ADVICE:
- Pot life of mixture: 4 to 6 hours depending on ambient temperature and humidity.
- Stirring regularly will stabilise the viscosity of the mixture.
- Do not dilute.

TECHNICAL SPECIFICATIONS:
Physical state: liquid
Colour: colourless
Odour: odourless
Flash point: > 160 °C
VOC content: 0 g/L

STORAGE:
The product can be stored up to 24 months in dry conditions and in its original packaging.

PACKAGING:
Bottle 100 ml, 0,5 L and 1 L, jerrycan 5 L

PROVIDED BY:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.

Consult the safety sheet before use.
Date TDS: 08/08/16

MUYLLE FACON

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.
Ambachtenstraat 58 - B-8870 Izegem
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78
info@muyllefacon.be - **www.rubiomonocoat.com**